



RS232

PIN	NAME
1	VCC
2	RX
3	TX
4	GND

NOTES:

- DRIVE METHOD: 1/16DUTY, 1/5BIAS,VOP4.5V.
- VIEWING ANGLE: 6 O'CLOCK. (封口在左)
- DISPLAY TYPE:STN(BLUE),TRANSMISSIVE/NEGATIVE.
- OPERATING TEMP:-20 TO 70°C.
- STORAGE TEMP: -30 TO 80°C.
- CONNECTION: ZEBRA.
- BACKLIGHT: WHITE/EDGE.
- INTERFACE: RS232
- NOT DIMENSION TOLERANCES IS ±0.3.

日期	版本	修改内容
170215	00	依GFC1602G/STN/Blue + 後板設計RS232
170222	01	1.因走線空間問題~將前後板的公座母座修改PITCH為1.27mm,並修正位置。 2. PCB前板與後板間距變更, 7.2→7.4mm
170223	02	PCB前板與後板間距變更回 7.2mm

晶發科技股份有限公司
GIFAR TECHNOLOGY CO., LTD

DATE	2017.02.23	REV	02	DRAWING NO.: R01-2017021501
UNIT: mm	Product: GFR1602GB-BNFEJSA			☉
SCALE: 1/1	DRAWN: Hazel	CHECKED: Donlin	PAGE: 1/1	