



Interface		
Pin no	Symbol	Function
1	VSS	Power supply (GND)
2	VDD	Power supply(+)
3	VO	Contrast Adjustmt
4	RS	Data / Instruction select
5	R/W	Read / Write select
6	E	Enable signal
7	DB0	Date bus line
8	DB1	Date bus line
9	DB2	Date bus line
10	DB3	Date bus line
11	DB4	Date bus line
12	DB5	Date bus line
13	DB6	Date bus line
14	DB7	Date bus line
15	LEDA	LED B/L (+)
16	LEDK	LED B/L (-)

Feature			
Controller	ST7066U	Module	122.0 x 33.0
Duty	1/16 duty	Viewing Area	99.0 x 13.0
Bias	1/5 bias	Mounting hole	115.0 x 25.0
B/L	Y/G	Character Size	4.85 x 9.66

Absolute Maximum Rating					
I tem	Symbol	Condition	Min	Max	Units
Supply for logic voltage	Vdd-Vss	25°c	-0.3	7	V
LCD driving supply voltage	Vdd-Vss	25°c	-0.3	13	V
Input voltage	Vin	25°c	-0.3	Vdd+0.3	V

Electrical Characteristics						
Item	Symbol	Condition	Min.	Typ.	Max.	Units
Power supply voltage	Vdd-Vss	25°c	4.5	-	5.5	V
LCD operation voltage	Vop	25°c	-	4.5	-	V
EL Forward Voltage(Y/G)	VF	25°c	-	4.2	-	V
EL Forward Current(Y/G)	IF	25°c	-	20	-	mA