



**NOTES:**

- DRIVE METHOD: 1/16DUTY, 1/5BIAS,VOP4.5V±0.3V, VDD5.0V.
- VIEWING ANGLE: 6 O'CLOCK. (封口在左)
- DISPLAY TYPE:STN(Y/G),TRANSFLECTIVE/POSITIVE.
- OPERATING TEMP:-20 TO 70°C.
- STORAGE TEMP: -30 TO 80°C.
- CONNECTION: ZEBRA.
- BACKLIGHT: YELLOW GREEN/EDGE.
- IC: SPLC780D1-001A/SPLC100B1
- NOT DIMENSION TOLERANCES IS ±0.3.

PIN	NAME
1	VSS
2	VDD(+5V)
3	VO
4	RS
5	R/W
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	LEDK
16	LEDA

日期	版本	修改内容
171103	00	依GFC1602GB-BNFEJPA修改YG玻璃與背光，新編料號GFC1602GB-YPAEJPA

**晶發科技股份有限公司**  
**G1 FAR TECHNOLOGY CO., LTD.**

<b>DATE</b>	2017.11.03	<b>REV</b>	00	<b>DRAWING NO. :</b>	R01-2017110302
<b>UNIT : mm</b>	<b>Product :</b> GFC1602GB-YPAEJPA				
<b>SCALE : 1/1</b>	<b>DRAWN :</b>	Hazel	<b>CHECKED :</b>	Sidney	<b>PAGE : 1/1</b>